



Online Data Sheet

Encoder WDG 100G


www.wachendorff-automation.com/wdg100g

Wachendorff Automation

... systems and encoders

- Complete systems
- Industrial rugged encoders to suit your application
- Standard range and customer versions
- Maximum permissible loads
- 48-hour express production
- Made in Germany
- Worldwide distributor network

Encoder WDG 100G (optical)



- Rugged and extremely thin thru-bore encoder for extension on power motors
- Thru-Bore, bore size max. 45 mm
- Full connection protection with 10 VDC up to 30 VDC
- Easy mounting
- Meets protection class IP50
- Up to 20,480 PPR
- Optional: -40 °C up to +80 °C

www.wachendorff-automation.com/wdg100g

Resolution

Pulses per revolution PPR up to 20480 PPR

Mechanical Data

Housing

Flange	hollow shaft (through-bored)
Flange material	aluminum
Housing cap	aluminum
Torque supports	incl. 1 torque support FEFB00H013-ZVK
- 1. Spring plate compensation	axial: ±1 mm, radial: ±0.5 mm
Housing	Ø 100 mm

Shaft(s)

Shaft material	stainless steel
Starting torque	approx. 1.5 Ncm at ambient temperature
Fixing	2 x M4, DIN 913; Starting torque: 2,5 Nm

Shaft Ø 25 mm

Shaft length L: 42 mm

Insertion depth min. 29 mm

Max. Permissible shaft loading radial 200 N

Max. Permissible shaft loading axial 100 N

Shaft Ø 25.4 mm, Ø 1"

Shaft length L: 42 mm, L: 1.65 in

Insertion depth min. 29 mm

Max. Permissible shaft loading radial 200 N, 20.39 kp

Max. Permissible shaft loading axial 100 N, 10.197 kp

Shaft Ø 28 mm

Shaft length L: 42 mm

Insertion depth min. 29 mm

Max. Permissible shaft loading radial 200 N

Max. Permissible shaft loading axial 100 N

Shaft Ø 30 mm

Shaft length L: 42 mm

Insertion depth min. 29 mm

Max. Permissible shaft loading radial 200 N

Max. Permissible shaft loading axial 100 N

Shaft Ø 32 mm

Shaft length L: 42 mm

Insertion depth min. 29 mm

Max. Permissible shaft loading radial 200 N

Max. Permissible shaft loading axial 100 N

Shaft Ø 36 mm

Shaft length L: 42 mm

Insertion depth min. 29 mm

Max. Permissible shaft loading radial 200 N

Max. Permissible shaft loading axial 100 N

Shaft Ø 38 mm

Shaft length L: 42 mm

Insertion depth min. 29 mm

Max. Permissible shaft loading radial 200 N

Max. Permissible shaft loading axial 100 N

Shaft Ø 40 mm

Shaft length L: 42 mm

Insertion depth min. 29 mm

Max. Permissible shaft loading radial 200 N

Max. Permissible shaft loading axial 100 N

Shaft Ø 42 mm

Shaft length L: 42 mm

Insertion depth min. 29 mm

Max. Permissible shaft loading radial 200 N

Max. Permissible shaft loading axial 100 N

Shaft Ø 45 mm

Shaft length L: 42 mm

Insertion depth min.	29 mm
Max. Permissible shaft loading radial	200 N
Max. Permissible shaft loading axial	100 N

Bearings

Bearings type	2 precision ball bearings
Nominal service life	3 x 10 ¹⁰ revs. at 100 % rated shaft load 1 x 10 ¹¹ revs. at 40 % rated shaft load 1 x 10 ¹² revs. at 20 % rated shaft load
Max. operating speed	1500 rpm

Machinery Directive: basic data safety integrity level

MTTF _d	200 a
Mission time (TM)	25 a
Nominal service life (L10h)	1 x 10 ¹² revs. at 20 % rated shaft load and 1500 rpm
Diagnostic coverage (DC)	0 %

Electrical Data

Power supply/Current consumption	4,75 VDC up to 5,5 VDC: typ. 100 mA
Power supply/Current consumption	5 VDC up to 30 VDC: typ. 70 mA
Power supply/Current consumption	10 VDC up to 30 VDC: typ. 100 mA
Output circuit	TTL TTL, RS422 compatible, inv. HTL HTL, inv. 1 Vpp sin/cos
Pulse frequency	TTL ≤ 5000 ppr: max. 200 kHz HTL ≤ 5000 ppr: max. 200 kHz TTL more than 1200 ppr: max. 2 MHz HTL more than 1200 ppr: max. 600 kHz 1 Vpp sin/cos: max. 100 kHz
Channels	AB ABN and inverted signals
Load	max. 40 mA / channel @ 1 Vpp sin/cos: min. 120 Ohm
Circuit protection	circuit type H24 and R24 only

Accuracy

Phase offset	90° ± max. 7.5 % of the period duration
pulse-/pause-ratio	≤5000 ppr: 50 % ± max. 7 % Output circuits F24, P24, F05, P05, 645: 50 % ± max. 10 %

Environmental data

ESD (DIN EN 61000-4-2):	8 kV
Burst (DIN EN 61000-4-4):	2 kV
includes EMC:	DIN EN 61000-6-2 DIN EN 61000-6-3
Vibration: (DIN EN 60068-2-6)	50 m/s ² (10 Hz up to 2000 Hz)
Shock: (DIN EN 60068-2-27)	1000 m/s ² (6 ms)
Design:	according DIN VDE 0160

Duty information

Customs tariff number:	90318020
Country of origin:	Germany

General Data


Weight	approx. 720 g
Connections	cable or connector, radial
Protection rating (EN 60529)	IP50
Operating temperature	-20 °C up to +80 °C 1 Vpp: -10 °C up to +70 °C
Storage temperature	-30 °C up to +80 °C

More Information

General technical data and safety instructions
<http://www.wachendorff-automation.com/gtd>

Options
<http://www.wachendorff-automation.com/acc>


Cable connection K3, L3 with 2 m cable




Description		ABN inv. poss.
K3	radial, shield not connected	•
L3	radial, shield connected to encoder housing	•

Assignments				
	K3, L3	K3, L3	L3	L3
Circuit	F05, H05, F24, H24, H30	P05, R05, P24, R24, 245, 645, R30	SIN	SIF
GND	WH	WH	WH	WH
(+) Vcc	BN	BN	BN	BN
A	GN	GN	GN	GN
B	YE	YE	GY	GY
N	GY	GY	BK	BK
Light reserve warning	-	-	-	RD
A inv.	-	RD	YE	YE
B inv.	-	BK, (BU at ACA)	PK	PK
N inv.	-	VT	VT	VT
Shield	flex	flex	flex	flex


Connector (M16x0.75) S3, 7-pin



Description	ABN inv. poss.
S3 radial, 7-pin, Connector connected to encoder housing	-

Assignments	
	S3
	7-pin
	
Circuit	F05, H05, F24, H24, H30
GND	1
(+) Vcc	2
A	3
B	4
N	5
Light reserve warning	-
A inv.	-
B inv.	-
N inv.	-
n. c.	6, 7
Shield	-


Connector (M23) S5, 12-pin



Description	ABN inv. poss.
S5 radial, 12-pin, Connector connected to encoder housing	•

Assignments				
	S5	S5	S5	S5
	12-pin	12-pin	12-pin	12-pin
Circuit	F05, H05, F24, H24, H30	P05, R05, P24, R24, 245, 645, R30	SIN	SIF
GND	10	10	10	10
(+) Vcc	12	12	12	12
A	5	5	5	5
B	8	8	8	8
N	3	3	3	3
Light reserve warning	-	-	-	7
A inv.	-	6	6	6
B inv.	-	1	1	1
N inv.	-	4	4	4
n. c.	1, 2, 4, 6, 7, 9, 11	2, 7, 9, 11	2, 7, 9, 11	2, 9, 11
Shield	-	-	-	-


Connector (M23) S5R, 12-pin (clockwise)



Description	ABN inv. poss.
S5R radial, 12-pin, Connector connected to encoder housing	•

Assignments				
	S5R	S5R	S5R	S5R
	12-pin	12-pin	12-pin	12-pin
Circuit	F05, H05, F24, H24, H30	P05, R05, P24, R24, 245, 645, R30	SIN	SIF
GND	10	10	10	10
(+) Vcc	12	12	12	12
A	5	5	5	5
B	8	8	8	8
N	3	3	3	3
Light reserve warning	-	-	-	7
A inv.	-	6	6	6
B inv.	-	1	1	1
N inv.	-	4	4	4
n. c.	1, 2, 4, 6, 7, 9, 11	2, 7, 9, 11	2, 7, 9, 11	2, 9, 11
Shield	-	-	-	-

Sensor-connector (M12x1) SC, 4-, 5-, 8-, 12-pin



Description	ABN inv. poss.
SC4 radial, 4-pin, Connector connected to encoder housing	-
SC5 radial, 5-pin, Connector connected to encoder housing	-
SC8 radial, 8-pin, Connector connected to encoder housing	•
SC12 radial, 12-pin, Connector connected to encoder housing	•

Assignments							
	SC4	SC5	SC8	SC8	SC8	SC12	SC12
	4-pin	5-pin	8-pin	8-pin	8-pin	12-pin	12-pin
Circuit	F05, H05, F24, H24, H30	F05, H05, F24, H24, H30	F05, H05, F24, H24, H30	P05, R05, P24, R24, R30, 245, 645	SIN	F05, H05, F24, H24, H30	P05, R05, P24, R24, 245, 645, R30
GND	3	3	1	1	1	3	3
(+) Vcc	1	1	2	2	2	1	1
A	2	4	3	3	3	4	4
B	4	2	4	4	5	6	6
N	-	5	5	5	7	8	8
Light reserve warning	-	-	-	-	-	-	-
A inv.	-	-	-	6	4	-	9
B inv.	-	-	-	7	6	-	7
N inv.	-	-	-	8	8	-	10
n. c.	-	-	6, 7, 8	-	-	2, 5, 7, 9, 10, 11, 12	2, 5, 11, 12
Shield	-	-	-	-	-	-	-

Options

Low temperature

Order key

The encoder WDG 100G with the output circuit types F24, H24, P24, R24, F05, H05, P05, R05, 245, 645 is also available with the extended temperature range -40 °C up to +80 °C (measured at the flange).

ACA

Cable length

Order key

The encoder WDG 100G can be supplied with more than 2 m cable. The maximum cable length depends on the supply voltage and the frequency; see www.wachendorff-automation.com/atd

XXX = Decimeter

Please extend the standard order code with a three figure number, specifying the cable length in decimetres.

Example: 5 m cable = 050

Example Order No.	Type						Your encoder
WDG 100G	WDG 100G						WDG 100G
	Bore size						
25	25; 1Z= Ø 25.4 mm, Ø 1"; 28; 30; 32; 36; 38; 40; 42; 45						
	Pulses per revolution PPR:						
1024	512, 1024, 2048, 2500, 3600, 4096, 4500, 5000, 8192, 10240, 16384, 20480 1 Vpp Sin/Cos only 1024, 2048 Other PPRs on request						
	Channels:						
ABN	AB, ABN						
	Output circuit						
H24	Resolution PPR	Power supply VDC	Output circuit	Light reserve warning	Order key		
	up to 2500	5 - 30	HTL (TTL at 5 VDC)	-	H30		
		5 - 30	HTL, inv. (TTL/RS422 comp. at 5 VDC)	-	R30		
	up to 5000	4.75 - 5.5	TTL	-	H05		
		4.75 - 5.5	TTL, RS422 comp., inverted	-	R05		
		10 - 30	HTL	-	H24		
		10 - 30	HTL inverted	-	R24		
		10 - 30	TTL, RS422 comp., inverted	-	245		
		8192 up to 20480	4.75 - 5.5	TTL	-	F05	
	8192 up to 20480	4.75 - 5.5	TTL, RS422 comp., inverted	-	P05		
		10 - 30	HTL	-	F24		
		10 - 30	HTL inverted	-	P24		
		10 - 30	TTL, RS422 comp., inverted	-	645		
	1024, 2048	4.75 - 5.5	1 Vpp sin/cos	•	SIF		
		4.75 - 5.5	1 Vpp sin/cos	-	SIN		
	Electrical connections						
K3	Description	ABN inv. poss.			Order key		
	Cable: length (2 m standard, WDG 58T: 1 m)						
	radial, shield not connected	•			K3		
	radial, shield connected to encoder housing	•			L3		
	Connector: (shield connected to encoder housing)						
	connector, M16x0.75, 5-pin, radial	-			SH5		
	connector, M16x0.75, 6-pin, radial	-			SH6		
	connector, M16x0.75, 8-pin, radial	•			SH8		
	connector, M16x0.75, 12-pin, radial	•			SH12		
	connector, M16x0.75, 7-pin, radial	-			S3		
	connector, M23, 12-pin, radial	•			S5		
	connector, clockwise pin count, M23, 12-pin, radial	•			S5R		
	sensor-connector, M12x1, 4-pin, radial	-			SC4		
	sensor-connector, M12x1, 5-pin, radial	-			SC5		
	sensor-connector, M12x1, 8-pin, radial	•			SC8		
	sensor-connector, M12x1, 12-pin, radial	•			SC12		
	Options						
	Description	Order key					
	Low temperature	ACA					
	Without option	Empty					
	Cable length	XXX = Decimeter					

Example Order No. =	WDG 100G	25	1024	ABN	H24	K3			WDG 100G							Your encoder
----------------------------	----------	----	------	-----	-----	----	--	--	----------	--	--	--	--	--	--	---------------------



For further information please contact our local distributor.
Here you find a list of our distributors worldwide.
<https://www.wachendorff-automation.com/contact-sales-en/>



Wachendorff Automation GmbH & Co. KG
Industriestrasse 7 • 65366 Geisenheim
Germany

Phone: +49 67 22 / 99 65 25
E-Mail: wdg@wachendorff.de
www.wachendorff-automation.de

